


適用機型	CPU系列	盒裝參考料號	規格									
			核心/執行緒	速度 GHz	L2	內含顯示功能-頻率	插槽	DDR3	製程	超頻		
桌上型	Core i7 Extreme Edition	<b>i7-3960X</b> BX80619I73960X	6/12	3.30 ~ 3.90	15M	-	LGA2011	4 ch	32奈米	V		
	Core i7	<b>i7-3930K</b> BX80619I73930K	6/12	3.20~3.80	12M	-	LGA2011	4 ch	32奈米	V		
		<b>i7-3820</b> BX80619I73820	4/8	3.60~3.90	10M	-	LGA2011	4 ch	32奈米	-		
		<b>i7-3770K</b> BX80637I73770K	4/8	3.50 ~ 3.90	8M	HD4000	LGA1155	2ch	22奈米	V		
		<b>i7-3770</b> BX80637I73770		3.40 ~ 3.90						-		
		Core i5	<b>i5-3570K</b> BX80637I53570K	4/8	3.40 ~ 3.80	6M	HD2500	LGA1155	2 ch	22奈米	V	6/13 到貨
		<b>i5-3570</b> BX80637I53570	3.40 ~3.80		-							
		<b>i5-3550</b> BX80637I53550	3.40 ~ 3.80		-							
			<b>i5-3470</b> BX80637I53470	4/4	3.20 ~ 3.60	6M	-	LGA1155	2 ch	32奈米	-	6/13 到貨
		<b>i5-3450</b> BX80637I53450	3.10 ~ 3.50									
			<b>i5-2550K</b> BX80623I52550K	4/4	3.40 ~ 3.80	6M	-	LGA1155	2 ch	32奈米	V	
			<b>i5-2320</b> BX80623I52320		3.00 ~ 3.30	6M	HD2000	LGA1155	2 ch	32奈米	-	
		Core i3	<b>i3-2130</b> BX80623I32130	2/4	3.40	3M	HD2000	LGA1155	2ch	32奈米	-	
			<b>i3-2125</b> BX80623I32125		3.30		HD3000					
			<b>i3-2120</b> BX80623I32120		3.30		HD2000					
		Pentium	<b>G870</b> BX80623G870	2/2	3.10	3M	HD	LGA1155	2ch	32奈米	-	
			<b>G860</b> BX80623G860		3.00							
			<b>G850</b> BX80623G850		2.90							
			<b>G840</b> BX80623G840		2.80							
			<b>G640</b> BX80623G640		2.80							
			<b>G630</b> BX80623G630		2.70							
			<b>G620</b> BX80623G620		2.60							
		Celeron	<b>G550</b> BX80623G550	2/2	2.60	2M	HD	LGA1155	2ch	32奈米	-	6/13 到貨
			<b>G540</b> BX80623G540		2.50							
			<b>G530</b> BX80623G530		2.40							
			<b>G460</b> BX80623G460	1/2	1.80	1.5M	HD	LGA1155	2ch	32奈米	-	出清
	風扇	BXRTS2011AC	 LGA2011 腳位適用,(非水冷式) 一般風扇									

\* 產品價格、規格及交易相關資訊概以經銷商下單前，聯強業務單位最後確認之資料為準。